

DuPont™ Cyrel® FAST 1001 TD

Thermal Flexographic Plate Processor

DuPont™ Cyrel® FAST 1001 TD is a plate making system that uses dry, thermal technology to process high quality photopolymer plates, thus eliminating all solvents and aqueous solutions from the plate room.

Benefits

- Maximum plate size 36" x 48" (900 x 1,200 mm)
- Extremely rapid access time
- Redesigned and streamlined for improved thermal management, dimensional stability and efficiency.
- Can handle small plate sizes
- Sleeker ergonomic design- with integrated control panel and an extended support tray to prevent plate drag and contamination.

Features

The Cyrel® FAST 1001 TD allows the production of Cyrel® FAST finished plates of up to a format of 36" x 48" (900 x 1,200 mm) in less than one hour, including the imaging and exposing steps, making it the ideal just-in-time plate making system for the market.

The 1001 TD has a redesigned heating roll designed to provide uniform heating across the plate. This optimized thermal management results in improved thin gauge plate clean-out, more consistent relief depth and a more uniform floor.

Additional laydown rollers maximize contact between the plate and the heater drum. This improved contact uniformity provides better plate dimensional stability and nearly eliminates scuff marks.

The new digital modem- allows remote troubleshooting and diagnostics 24/7 and software upgrades to be automatically uploaded. Software upgrades optimize thermal profiles for multiple plate types.



The Cyrel® FAST 1001 TD delivers outstanding plate quality and uniformity. This processor has the ability to produce a finished plate without solvent washout. The wide format Cyrel® 1000 ECLF for exposing the light-finishing plates is available to complement the Cyrel® FAST 1001 TD as an all-round system solution. As with all elements of the Cyrel® FAST system, it is environmentally friendly with no solvents to handle, store or recycle and no drying equipment is required.

Cyrel® FAST system technology enhances the production of high quality plates quickly, by combining the efficiency and speed of digital plate imaging with the productivity and environmental benefits of dry, thermal plate processing.

DuPont™ Cyrel® FAST 1001 TD

Thermal Flexographic Plate Processor

Technical Data

General	Details	Other Notes
Equipment Name	DuPont™ Cyrel® FAST 1001 TD	Thermal developer (water cooled drum)
SAP Article Number	D15333970	
Max. Nominal Plate Width	36" (914 mm)	
Min. Nominal Plate Width	10" (254 mm)	
Max. Nominal Plate Length	48" (1,219 mm)	
Max. Plate Thickness	0.045" to 0.112"	1.14 mm to 2.84 mm
Electrical (Field Configurable)	220 / 240 Volt – 50 / 60 hz	1PH / PE
Power (Nominal)	7.1 kW	
Current (Nominal Load)	32 Amp @ 230 Volt	
Connecting Wires	230 Volt configuration	3 x 6 mm ²
Grounding	≤ 0.1 Ω	Ground bar to equipment frame and to electrical supply ground
Exhaust	Ø 5.0" (127 mm)	213 m ³ / h (min)
Environmental Data	Temperature range: 65°F to 80°F (18°C to 27°C)	Relative humidity from 40% to 60% non-condensing
Compressed Air Supply	6.9 bar min	100 psi min
Dimensions	Uncrated	Crated
D	66.04" (1,677.42 mm)	80" (2,032 mm)
W	73.33" (1,862.58 mm)	87" (2,210 mm)
H	45.32" (1,151.13 mm)	65" (1,651 mm)
Weight	4,105 kg (9,050 lbs)	4,990 kg (11,000 lbs)
Color	DuPont Grey & DuPont Red	

DuPont Industrial Solutions brings together leading technologies and products for the printing and package printing industries. DuPont™ Cyrel® is one of the world's leading flexographic platemaking systems in digital and conventional formats, including DuPont™ Cyrel® brand photopolymer plates (analog and digital), Cyrel® platemaking equipment, Cyrel® round sleeves, Cyrel® plate mounting systems and the revolutionary Cyrel® FAST thermal system.



cyrel.com/na

For more information on DuPont™ Cyrel® or other DuPont products, please visit our website.

The information provided in this data sheet corresponds to our knowledge on the subject at the date of its publication. It may be subject to revision as new knowledge and experience becomes available. This information is not intended to substitute for any testing you may need to conduct to determine for yourself the suitability of our products for your particular purposes. Since we cannot anticipate all variations in end-use and disposal conditions, DuPont makes no warranties and assumes no liability in connection with any use of this information. It is intended for use by persons having technical skill, at their own discretion and risk. Nothing in this publication is to be considered as a license to operate under or a recommendation to infringe any patent right.

DuPont™, the DuPont Oval Logo, and Cyrel® are trademarks or registered trademarks of DuPont or its affiliates. Copyright © 2021 DuPont de Nemours Inc. All rights reserved.

PDS-NA0043-EN (4/21)