

DuPont™ Cyrel® 1000 ECDLF

Exposure, Dryer & Light Finisher

DuPont™ Cyrel® 1000 ECDLF exposes, dries, post-exposes and finishes high quality photopolymer plates up to a format of 900 x 1,200 mm (36" x 48").

Benefits

- Maximum plate size 900 x 1,200 mm (36" x 48")
- Clamshell design
- Anodised temperature controlled exposure bed
- Light integrator controlled exposure
- All-in-one exposure, dryer & light finisher
- Optimum productivity

Features

The Exposure section is a clamshell design holding 24 UV-A fluorescent tubes with built-in reflectors. One yellow control tube illuminates the exposure bed for inspecting of the plate surface. Unique to this exposure unit is the anodised temperature controlled bed, closed loop system that controls the exposure bed temperature, which translates into predictable and consistent exposures. The unit is fitted with a light integrator that compensates for the decrease in light output as the tubes age. To meet the demanding needs of high quality plates the user can easily customise the 20 basic exposure set-ups.

Each tube is constantly monitored by a photo-sensor. If the light emission of one or more tubes decreases below a set point, the user is alerted. There are three counters imbedded in the PLC to keep track of the number of hours the UV-A and UV-C tubes have been in operation.



The four dryer drawers are located beneath the Light Finisher section. There is one timer per dryer drawer for regulating the temperature. Automatic blowers on both dryer drawers further control the set temperature. The exhaust air-flow is monitored by a safety sensor.

The Post Exposure and Light Finisher section hold 19 UV-C and 20 UV-A tubes. The PLC allows the user to perform post exposure and finishing in a preferred sequence, or simultaneously. The post exposure and finisher section has 20 basic set-ups that can be easily customised by the user.

DuPont™ Cyrel® 1000 ECDLF

Exposure, Dryer & Light Finisher

Technical Data

General	Details	Other Notes
Equipment Name	DuPont™ Cyrel® 1000 ECDLF	Cooled exposure, dryer, post exposure and light finisher
SAP Article Number	D11552085	
Plate Thickness	0.5 mm to 7.0 mm	0.019" to 0.27"
Max. Nominal Plate Width	900 mm (36")	
Max. Nominal Plate Length	1,200 mm (48")	
UV-A Tubes Wave Length	360 nm – 380 nm	24 tubes (Exposure); 20 tubes (Light Finisher)
UV-C Tubes Wave Length	254 nm	19 tubes (Light Finisher)
Electrical (Field Configurable)	370 / 440 Volt – 50 / 60 hz 208 / 240 Volt – 50 / 60 hz	3Ph / N / PE 3Ph / PE
Power (nominal)	9.5 kW	
Current (Nominal Load)	15 Amp @ 400 Volt; 28 Amp @ 230 Volt	
Connecting Wires	400 Volt configuration; 230 Volt configuration	5 x 2.5 mm ² ; 4 x 6 mm ²
Exhaust (Light Finisher)	Ø 140 mm (5.5")	800 m ³ / h-470.9 scfm (min)
Exhaust (Dryer)	Ø 60 mm (2.36")	100 m ³ / h-58.86 scfm (min)
Environmental Data	Temperature range: 17°C to 28°C (63°F to 82°F)	Relative humidity from 20% to 80% non-condensing
Compressed Air Supply	7 bar minimum	
Dimensions	Uncrated	Crated
L	1,550 mm (61.1")	1,650 mm (65.0")
W	1,800 mm (70.9")	1,900 mm (74.8")
H	1,090 mm (42.9")	1,500 mm (59.1")
H (open)	1,850 mm (72.9")	
Weight	650 kg (1,433 lbs)	920 kg (2,028 lbs)
Color	DuPont Grey & DuPont Red	

DuPont Industrial Solutions brings together leading technologies and products for the printing and package printing industries. DuPont™ Cyrel® is one of the world's leading flexographic platemaking systems in digital and conventional formats, including DuPont™ Cyrel® brand photopolymer plates (analogue and digital), Cyrel® platemaking equipment, Cyrel® round sleeves, Cyrel® plate mounting systems and the revolutionary Cyrel® FAST thermal system.



cyrel.eu

For more information on DuPont™ Cyrel® or other DuPont products, please visit our website.

The information provided in this data sheet corresponds to our knowledge on the subject at the date of its publication. It may be subject to revision as new knowledge and experience becomes available. This information is not intended to substitute for any testing you may need to conduct to determine for yourself the suitability of our products for your particular purposes. Since we cannot anticipate all variations in end-use and disposal conditions, DuPont makes no warranties and assumes no liability in connection with any use of this information. It is intended for use by persons having technical skill, at their own discretion and risk. Nothing in this publication is to be considered as a license to operate under or a recommendation to infringe any patent right.

DuPont™, the DuPont Oval Logo, and Cyrel® are trademarks or registered trademarks of DuPont or its affiliates. Copyright © 2021 DuPont de Nemours Inc. All rights reserved.

PDS-EU0005-EN (3/21)