

# DuPont™ Cyrel® 3000 EC

Exposure

**DuPont™ Cyrel® 3000 EC exposes high quality photo-polymer plates up to a format of 1,320 x 2,030 mm (52" x 80").**

## Benefits

- Maximum plate size 1,320 x 2,030 mm (52" x 80")
- Clamshell design
- Anodised temperature controlled exposure bed
- Light integrator controlled exposure
- Outstanding vacuum draw down
- Optimum productivity

## Features

The clamshell design holds 48 UV-A fluorescent tubes with built-in reflectors. One yellow control tube illuminates the exposure bed for inspecting of the plate surface. Unique to this exposure unit is the anodised temperature controlled bed, closed loop system that controls the exposure bed temperature, which translates into predictable and consistent exposures. The unit is fitted with a light integrator that compensates for the decrease in light output as the tubes age. To meet the demanding needs of high quality plates the user can easily customise the 25 basic exposure set-ups.

Each tube is constantly monitored by a photo-sensor. If the light emission of one or more tubes decreases below a set point, the user is alerted. There is a counter imbedded in the PLC to keep track of the number of hours the UV-A tubes have been in operation.



# DuPont™ Cyrel® 3000 EC

Exposure

## Technical Data

General	Details	Other Notes
<b>Equipment Name</b>	DuPont™ Cyrel® 3000 EC	Cooled exposure, Clam shell
<b>SAP Article Number</b>	D13290547	
<b>Plate Thickness</b>	0.5 mm to 7.0 mm	0.019" to 0.27"
<b>Max. Nominal Plate Width</b>	1,320 mm (52")	
<b>Max. Nominal Plate Length</b>	2,030 mm (80")	
<b>UV-A Tubes Wave Length</b>	360 nm – 380 nm	48 tubes
<b>UV-C Tubes Wave Length</b>	NA	
<b>Electrical (Field Configurable)</b>	370 / 440 Volt – 50 / 60 hz 208 / 240 Volt – 50 / 60 hz	3Ph / N / PE 3Ph / PE
<b>Power (nominal)</b>	10 kW	
<b>Current (Nominal Load)</b>	16 Amp @ 400 Volt; 27 Amp @ 230 Volt	
<b>Connecting Wires</b>	400 Volt configuration; 230 Volt configuration	5 x 10 mm <sup>2</sup> ; 4 x 10 mm <sup>2</sup>
<b>Exhaust (Light Finisher)</b>	NA	
<b>Environmental Data</b>	Temperature range: 17°C to 28°C (63°F to 82°F)	Relative humidity from 20% to 85% non-condensing
<b>Compressed Air Supply</b>	7 bar minimum	
<b>Dimensions</b>	<b>Uncrated</b>	<b>Crated</b>
<b>D</b>	2,110 mm (83.1")	2,310 mm (90.6")
<b>W</b>	3,300 mm (129.9")	3,580 mm (141.0")
<b>H</b>	2,015 mm (79.4")	2,430 mm (91.0")
<b>H - open</b>	2,650 mm (104.3")	
<b>Weight</b>	1,860 kg (4,101 lbs)	2,360 kg (5,203 lbs)
<b>Colour</b>	DuPont Grey & DuPont Red	

DuPont Industrial Solutions brings together leading technologies and products for the printing and package printing industries. DuPont™ Cyrel® is one of the world's leading flexographic platemaking systems in digital and conventional formats, including DuPont™ Cyrel® brand photopolymer plates (analogue and digital), Cyrel® platemaking equipment, Cyrel® round sleeves, Cyrel® plate mounting systems and the revolutionary Cyrel® FAST thermal system.



[cyrel.eu](http://cyrel.eu)

For more information on DuPont™ Cyrel® or other DuPont products, please visit our website.

The information provided in this data sheet corresponds to our knowledge on the subject at the date of its publication. It may be subject to revision as new knowledge and experience becomes available. This information is not intended to substitute for any testing you may need to conduct to determine for yourself the suitability of our products for your particular purposes. Since we cannot anticipate all variations in end-use and disposal conditions, DuPont makes no warranties and assumes no liability in connection with any use of this information. It is intended for use by persons having technical skill, at their own discretion and risk. Nothing in this publication is to be considered as a license to operate under or a recommendation to infringe any patent right.

DuPont™, the DuPont Oval Logo, and Cyrel® are trademarks or registered trademarks of DuPont or its affiliates. Copyright © 2021 DuPont de Nemours Inc. All rights reserved.

PDS-EU0017-EN (3/21)