

# DuPont™ Cyrel® 3000 ETL-i

Exposure Top Lift

**DuPont™ Cyrel® 3000 ETL-i exposes high quality photopolymer plates up to a maximum format of 1,320 x 2,030 mm (52" x 80").**

## Benefits

- Maximum plate size 1,320 x 2,030 mm (52" x 80")
- Top Lift design
- Double sided exposure
- Pre-heated back exposure lamps
- 360° plate access
- Optimum productivity

## Features

The automatic lifting of the exposure lid allows easy and convenient 360° access to the exposure bed and photopolymer plate. This 360° access simplifies cleaning and adjusting of negatives and increases efficiency.

The main exposure is performed with 44 UV-A fluorescent tubes with built-in reflectors that are located in the top lid. The user can customise up to 20 basic exposure set ups through the touch screen control panel.

The exposure unit also features programmable back exposures. To perform the back and main exposure, it is not required to flip the photopolymer plates. The back exposure is performed with 46 UV-A fluorescent tubes with built-in reflectors that are located underneath the exposure glass plate. Unique to this equipment is the pre-heating exposure section which translates into predictable and consistent back exposures.

Two yellow control tubes are used to illuminate the exposure bed while performing inspection of the plate surface.



# DuPont™ Cyrel® 3000 ETL-i

Exposure Top Lift

## Technical Data

General	Details	Other Notes
<b>Equipment Name</b>	DuPont™ Cyrel® 3000 ETL-i	Double side exposure frame including punch
<b>SAP Article Number</b>	D14092321	
<b>Max. Nominal Plate Width</b>	1,320 mm (52")	
<b>Max. Nominal Plate Length</b>	2,030 mm (80")	
<b>UV-A Tubes Wave Length</b>	360 nm – 380 nm	44 tubes top section (main exposure) 46 tubes bottom section (back exposure)
<b>UV-C Tubes Wave Length</b>	NA	
<b>Electrical (Field Configurable)</b>	400 Volt – 50 / 60 hz (+10%–5%) 230 Volt – 50 / 60 hz (+10%–5%)	3Ph / N / PE 3Ph / PE
<b>Power (nominal)</b>	12 kW	
<b>Current (Nominal Load)</b>	20 Amp @ 400 Volt; 30 Amp @ 230 Volt	
<b>Connecting Wires</b>	400 Volt configuration; 230 Volt configuration	5 x 6 mm <sup>2</sup> ; 4 x 6 mm <sup>2</sup>
<b>Grounding</b>	≤ 0.1 Ω	Ground bar to equipment frame and to electrical supply ground
<b>Exhaust</b>	NA	
<b>Environmental Data</b>	Temperature range: 17°C to 28°C (63°F to 82°F)	Relative humidity below 55%
<b>Compressed Air Supply</b>	7 Bar (100 PSI)	
<b>Dimensions</b>	<b>Uncrated</b>	<b>Crated</b>
<b>D</b>	2,180 mm (85.8")	2,280 mm (89.8")
<b>W</b>	3,300 mm (129.9")	3,510 mm (138.2")
<b>H</b>	2,140 mm (84.3")	2,450 mm (96.5")
<b>Weight</b>	1,420 kg (3,131 lbs)	2,300 kg (5,071 lbs)
<b>Colour</b>	DuPont Grey & DuPont Red	

DuPont Industrial Solutions brings together leading technologies and products for the printing and package printing industries. DuPont™ Cyrel® is one of the world's leading flexographic platemaking systems in digital and conventional formats, including DuPont™ Cyrel® brand photopolymer plates (analogue and digital), Cyrel® platemaking equipment, Cyrel® round sleeves, Cyrel® plate mounting systems and the revolutionary Cyrel® FAST thermal system.



[cyrel.eu](http://cyrel.eu)

For more information on DuPont™ Cyrel® or other DuPont products, please visit our website.

The information provided in this data sheet corresponds to our knowledge on the subject at the date of its publication. It may be subject to revision as new knowledge and experience becomes available. This information is not intended to substitute for any testing you may need to conduct to determine for yourself the suitability of our products for your particular purposes. Since we cannot anticipate all variations in end-use and disposal conditions, DuPont makes no warranties and assumes no liability in connection with any use of this information. It is intended for use by persons having technical skill, at their own discretion and risk. Nothing in this publication is to be considered as a license to operate under or a recommendation to infringe any patent right.

DuPont™, the DuPont Oval Logo, and Cyrel® are trademarks or registered trademarks of DuPont or its affiliates. Copyright © 2021 DuPont de Nemours Inc. All rights reserved.

PDS-EU0024-EN (3/21)