

# DuPont™ Cyrel® FAST Round EX 1450

Flexographic Sleeve Exposure Device

**DuPont™ Cyrel® FAST Round EX 1450 is a high productive flexographic sleeve exposure device which complements the Cyrel® FAST round system.**

## Benefits

- Maximum sleeve size 1,450 x 1,000 mm (57" x 39")
- Extremely rapid access time
- Smaller environmental footprint
- High-quality precision printing
- Higher durability for long print runs
- Robust and easy to support
- Optimum productivity
- Small equipment footprint

## Features

The Cyrel® FAST Round EX 1450 exposes a FAST round seamless photopolymer sleeve in less than 10 minutes independent of sleeve size.

Due to its vertical design and a high level of automation, the Cyrel® FAST Round EX 1450 is very operator friendly. Sleeve handling is easy since special tools are not required for fixation. Another benefit of the remarkable design is the small space requirement.

The technology enhances the production of high quality sleeves quickly, by combining the efficiency and speed of digital sleeve imaging with the productivity and environmental benefits of dry, thermal sleeve processing.

The digital sleeves for DuPont's thermal sleeve making process are designed to meet the needs of high quality plates with fine halftone, line-work and solids.



# DuPont™ Cyrel® FAST Round EX 1450

Flexographic Sleeve Exposure Device

## Technical Data

General	Details	Other Notes
<b>Equipment Name</b>	DuPont™ Cyrel® FAST Round EX 1450	Flexographic Sleeve Exposure Device
<b>SAP Article Number</b>	D14466727	
<b>Max. Nominal Sleeve Width</b>	1,450 mm (57")	
<b>Min. Nominal Sleeve Width</b>	300 mm (11.8")	
<b>Max. Nominal Sleeve Repeat</b>	1,000 mm (39.3")	
<b>Min. Nominal Sleeve Repeat</b>	330 mm (12.9")	
<b>Sleeve Thickness</b>	Thin 1,573 mm/Classic 3,165 mm	
<b>Electrical (Field Configurable)</b>	400 V ~ 3 / N / PE / 50/60 Hz	
<b>Power (Nominal)</b>	4 kW	
<b>Current (Nominal Load)</b>	7.5 A	
<b>Grounding</b>	16 mm <sup>2</sup> connection on frame	
<b>Exhaust</b>	Ø 100 mm (3.94")	max. 150 m <sup>3</sup> / h
<b>Environmental Data</b>	Temperature range: 18°C to 27°C (65°F to 80°F)	Relative humidity from 20% to 80% non-condensing
<b>Compressed Air Supply</b>		
<b>Dimensions</b>	<b>Uncrated</b>	<b>Crated</b>
<b>L</b>	1,900 mm (74.8")	2,240 mm (88.19")
<b>D</b>	818 mm (32.2")	1,200 mm (47.24")
<b>H</b>	2,277 mm (89.65")	2,540 mm (100")
<b>Weight</b>	500 kg (1,102 lbs)	870 kg (1,918 lbs)
<b>Colour</b>	DuPont Grey & DuPont Red	

DuPont Industrial Solutions brings together leading technologies and products for the printing and package printing industries. DuPont™ Cyrel® is one of the world's leading flexographic platemaking systems in digital and conventional formats, including DuPont™ Cyrel® brand photopolymer plates (analogue and digital), Cyrel® platemaking equipment, Cyrel® round sleeves, Cyrel® plate mounting systems and the revolutionary Cyrel® FAST thermal system.



[cyrel.eu](http://cyrel.eu)

For more information on DuPont™ Cyrel® or other DuPont products, please visit our website.

The information provided in this data sheet corresponds to our knowledge on the subject at the date of its publication. It may be subject to revision as new knowledge and experience becomes available. This information is not intended to substitute for any testing you may need to conduct to determine for yourself the suitability of our products for your particular purposes. Since we cannot anticipate all variations in end-use and disposal conditions, DuPont makes no warranties and assumes no liability in connection with any use of this information. It is intended for use by persons having technical skill, at their own discretion and risk. Nothing in this publication is to be considered as a license to operate under or a recommendation to infringe any patent right.

DuPont™, the DuPont Oval Logo, and Cyrel® are trademarks or registered trademarks of DuPont or its affiliates. Copyright © 2021 DuPont de Nemours Inc. All rights reserved.

PDS-EU0028-EN (3/21)